



O.M.F.

IMPIANTI DI FRANTUMAZIONE
INSTALLATIONS DE CONCASSAGE
CRUSHING PLANTS

MULINI REVERSIBILI A PERCUSSIONE **SERIE MTH**
BROYEURS REVERSIBLES A PERCUSSION **SERIE MTH**
REVERSIBLE IMPACT MILLS **SERIE MTH**





Mulini reversibili terziari atti al riciclaggio di graniglie, aventi dimensioni molto ridotte, anche dure e abrasive, per la produzione di sabbia di qualità

Broyeurs tertiaires réversibles adaptés au recyclage des graviers, ayants des très petites dimensions, même durs et abrasifs, pour la production de sable de qualité

Reversible tertiary mills suitable for the recycling of gravel, having very small dimensions, even hard and abrasive, for the production of quality sand

Modello	Apertura	Portata	Alimentazione	Potenza	Peso
Modèle	Ouverture	Débit	Alimentation	Puissance	Poids
Type	Opening	Capacity	Feeding	Power	Weight
	mm.	ton/h.	mm.	kW	Kg.
MTH 500	500x120	40 - 60	40	110,75 / 132,75	6.700
MTH 1000	1.000x120	90 - 120	40	251,50 / 316,50	12.500
MTH 500SPEEDY	500x120	30 - 50	40	133,35 / 161,35	7.400
MTH 1000SPEEDY	1.000x120	80 - 100	40	251,80 / 316,80	14.800